



Early Journal Content on JSTOR, Free to Anyone in the World

This article is one of nearly 500,000 scholarly works digitized and made freely available to everyone in the world by JSTOR.

Known as the Early Journal Content, this set of works include research articles, news, letters, and other writings published in more than 200 of the oldest leading academic journals. The works date from the mid-seventeenth to the early twentieth centuries.

We encourage people to read and share the Early Journal Content openly and to tell others that this resource exists. People may post this content online or redistribute in any way for non-commercial purposes.

Read more about Early Journal Content at <http://about.jstor.org/participate-jstor/individuals/early-journal-content>.

JSTOR is a digital library of academic journals, books, and primary source objects. JSTOR helps people discover, use, and build upon a wide range of content through a powerful research and teaching platform, and preserves this content for future generations. JSTOR is part of ITHAKA, a not-for-profit organization that also includes Ithaka S+R and Portico. For more information about JSTOR, please contact support@jstor.org.

represented here is therefore not without some historical interest.

Plate 39. — Wrought Iron Lantern, by Valerian Gillar, Art Metal Workers in Vienna.

The design of the lantern is made to correspond with the style of the Castle for which it was ordered. Ornaments and foliage are hammered by hand, the laurel branches wrought and chased, the frame work of the lantern made of angle iron, and forged together. The form being curved in plan on the four sides, the filling in of the thick bent glass required great exactness

of work. From a perpendicular iron pipe which goes through the lantern four brackets branch off in form of a moveable cross to hold four petroleum lamps, the lantern being hung up, and drawn up and down by means of chains and counter weight.

Plate 40. — Embroidery, 16th century work, in the *Musée Cluny* in Paris. Real size.

The embroidery, the middle part of a chasuble, is executed in appliqué work, silk on dark red velvet, lined with goldthreads, and in design and colour most perfect.

VARIOUS.

The Antiquity of Weaving.

The earliest records of the art of weaving are to be found in the Old Testament. Pharaoh arrayed Joseph in "vestures of fine linen", and Job lamented that his days were swifter than the weaver's shuttle, the use of the simile proving that the shuttle was a common and well known object at the time. Portions of woven cloth and a weaver's shuttle have been found among the remains of the Lake dwellings, and as the latter are believed to belong to the stone age, the origin of the art may possibly have been nearly coincident with the existence of man.

Few if any savage races have been discovered altogether ignorant of the art, and many of them have brought it to a considerable degree of perfection; while the relics of the ancient Peruvians and Egyptians show that they were skilled weavers. Some fragments of Egyptian cloth were found on examination to be woven with threads of about 100 hanks to the pound, with 140 threads to the inch in the warp, and 64 in the woof. Although the art was practised extensively, and with no mean skill, in very ancient times, it progressed slowly and gradually — by small steps at long intervals.

The great advances in the art of weaving have been made during the past 300 years, mainly during the past century.

Scientific American.

Stearate of Soda for Painting.

A new composition has recently been invented for use in painting. An alcoholic solution of stearate of soda is made in the proportion of 50 grammes of the salt in 1,000 grammes of 66 per cent alcohol. Solutions of soap in alcohol, more or less concentrated, may be used; but the stearate forms the most impenetrable and least costly material. The solution may be colored with aniline colors and yellow ochre. It takes well on wood, lime and cement.

Protection of Iron from Corrosion.

A new method of protecting iron from corrosion has recently been patented by Mr. J. B. A. Dode, in England. Its cost is about one third that of a coat of paint, one tenth that of electroplating with nickel and one twentieth of the ordinary process of painting and gilding. It can also be colored in a variety of ways. Iron treated in this way is said to be "platinized". The articles to be protected are coated with a thin film of borate of lead, containing a little caprous oxide solution and bright scales of precipitated platinum in suspension. They are then heated to redness and become covered with a thin, glassy, bright-gray coat, similar in appearance to polished iron. It is unaffected by sewer gas, dilute acids and alkalies, and the heat of the kitchen fire.

Scientific American.

Malleable Brass.

The brass alloy in most common use is probably that containing about 65 copper, 33 zinc, and 2 lead or tin. This compound works well in the lathe, and can be rolled, but is very imperfectly malleable. Recently, says the *Electrician*, a brass has been manufactured which possesses entirely novel properties, and can be forged at a red heat precisely like iron, so that it becomes applicable for many purposes for which ordinary brass is unsuitable. The new alloy is composed of 57 copper and 43 zinc; it should contain neither lead nor tin.

The Hectograph.

Herr Levitus, of Vienna, lately exhibited an arrangement called a "hectograph", for multiplying writing, which, though not directly connected with photography, may prove interesting. The hectograph consists of a flat sheet iron box, filled with a gluey mass upon which, after moistening and drying it several times, a sheet of paper, written upon with a specially prepared ink, is placed and lightly rubbed with the hand. When the paper is raised, the writing is found to be transferred reversed to the film of glue, and from that film, by simply placing pieces of dry paper upon it and rubbing them, some fifty impressions of the writing can be taken in a short time. The negative impression can easily be removed from the film by washing with warm water, and the latter can be used over and over again for a long time.

Scientific American.

Staining Floors.

The "London Furniture Gazette" commends the following method of staining floors in oak or walnut colors; put 1 oz. Vandyke brown in oil, 3 ozs. pearlash, and 2 drms. dragon's blood, into an earthenware pan or large pitcher; pour on the mixture 1 quart of boiling water; stir with a piece of wood. The stain may be used hot or cold. The boards should be smoothed with a plane and glass-papered; fill up the cracks with plaster of Paris; take a stiff brush, dip in the stain, and rub this in well; the brush should not be rubbed across the boards, but lengthwise. Only a small piece should be done at a time. By rubbing in one place more than another, an appearance of oak or walnut is more apparent; when quite dry the boards should be sized with glue size, made by boiling glue in water, and brushing it in the boards hot. When this is dry, the boards should be papered smooth and varnished with brown hard varnish or oak varnish; the brown hard varnish will wear better and dry quicker; it should be thinned with a little French polish, and laid on the boards with a smooth brush.